Industrial Pressure Gauges (Dry / Glycerine Filled)

Applications

- For pressure measurement of the fluids that will not corrosive effect on brass material (not with high density and solid particles fluids)
- Machine building industry
- Power plants
- Process industry
- Ship building industry

Sample Picture



General Features

- Production according to EN 837-1 standard
- Stainless steel case
- Filled version for the process with vibration
- Resistance to heavy working conditions

Standard Technical Features

Nominal size
100 mm, 160 mm

Design
EN 837 - 1

Ingress protection
IP65

Accuracy class
Cl. 1.0

Scale ranges
0 … 0,6 bar to 0 … 400 bar
-1 … 0 bar to -1 … +24 bar (vacuum-positive pressure)

Pressure limitation
Steady : 3/4 of full scale
Short time : ≤100 bar : 1.25 x full scale
>100 bar to ≤400 bar : 1.15 x full scale

Ambient temperature
H200 (dry version) : -20 … +60 °C
H200G (filled version) : -20 … +60 °C

Media temperature
H200 (dry version) : +60 °C maximum
H200G (filled version) : +60 °C maximum

Case
304 stainless steel

Bezel ring
304 stainless steel (Bayonet type)

Pointer
Black painted Aluminium DIN pointer

Dial
Aluminium with white background

Temperature effect
±0,04 x (t2 - t1) %full scale (must be added error limit)
t2 : media temperature t1 : +20 °C reference temperature

Standard Technical Features


Window
Toughened glass

Movement
304 stainless steel

Bourdon tube
Material : Copper alloy
≤ 100 bar : C type
> 100 bar : Helical type

Process connection
Material : Brass
100 mm : G 1/2 B (22 mm)
160 mm : G 1/2 B (22 mm)

Options
- Other process connections (1/2 NPT etc.)
- Other scale ranges (kg/cm², psi, MPa etc.)
- Calibration certificate
- Special customer dial design
- Drag pointer version (H200.SP_H200G.SP)



Dimensions (mm)												Weights (kg)	
Connection position	a	b	s	D	d	H	M	C	F	G	SW	H200	H200G
100 mm Lower Mount	18,00	49,00	-	101,00	99,00	139,00	-	-	-	G 1/2 B	22	0,55	0,80
160 mm Lower Mount	18,00	49,00	-	161,50	159,00	198,50	-	-	-	G 1/2 B	22	1,10	1,75
100 mm Lower Back Mount	18,00	49,00	-	101,00	99,00	-	93,00	-		G 1/2 B	22	0,55	0,80
160 mm Lower Back Mount	18,00	49,00	-	161,50	159,00	-	99,00	-	-	G 1/2 B	22	1,10	1,75
100 mm Back Flange Mount	18,00	54,00	5,30	101,00	99,00	156,00	-	116,00	132, 00	132, 00	G 1/2 B	22	0,65	0,90
160 mm Back Flange Mount	18,00	54,00	6,15	161,50	159,00	217,50	-	178,00	196,00	G 1/2 B	22	1,30	1,95
100 mm Front Flange Mount	21,50	51,50	6,15	101,00	99,00	-	96,50	116,00	130,00	G 1/2 B	22	0,65	0,90
160 mm Front Flange Mount	21,50	51,50	6,15	164,00	159,00	-	102,50	178,00	196,80	G 1/2 B	22	1,20	1,85
100 mm Panel Mount	21,50	51,50	-	101,00	99,00	-	96,50	-	107,50	G 1/2 B	22	0,80	1,05
160 mm Panel Mount	21,50	51,50	-	164,00	159,00	-	102,50	-	168,00	G 1/2 B	22	1,30	1,90

AK TEKNİK
FABRİKA MALZ. TİC. VE SAN. LTD. ŞTİ.
Meclis Mah. Atatürk Cad.
No.51/2-3 34785
Sancaktepe / İSTANBUL / TÜRKİYE
Tel: +90 216 314 20 50
www.aterma.com.tr
satis@aterma.com.tr